

Growatt ShineGPRS-X

- No strings attached, easy to use
- Mobile network, long range
- Universal mobile networks supported
- Online monitoring and maintenance



P O W E R
- I N G
T O M O R -
R R O W

Growatt

www.growatt.com

| Datasheet | ShineGPRS-X |
|-------------------------------|--|
| Wireless parameters | |
| Network type | GSM/GPRS |
| GSM/GPRS/EDGE frequency range | 850/900/1800/1900MHZ |
| Transmitting power | GSM850/GSM900: 2W DCS1800/PCS1900: 1W |
| Hardware parameters | |
| Serial port speed | 9600bps/115200bps |
| Operating voltage | 5V (+/-5%) |
| Operating current | 2A |
| Rating power | 5W |
| Operating temperature | -30°C ... +65°C |
| Ingress protection | IP65 |
| Application parameters | |
| Servers | ShineServer |
| Communication with Inverter | USB(Modbus RTU protocol) |
| Communication with server | TCP(Modbus TCP protocol) |
| Configuration interface | APP |
| SIM type | regular SIM card |
| Uploading interval | 5 Mins(1-15 adjustable) |
| Default server IP | server.growatt.com |
| General data | |
| Dimensions(L/H/W)mm | 122/32/47 |
| Weight | 70g |
| Language | English,Chinese |
| Warranty | 1 year |

CE