

Kensol Hydrobox KTHB Series

КТНВ

A module containing the most important hydraulic and electrical components of the heat pump system, cooperative with KENSOL heat pumps. This device speeds up the installation process while brightening up the boiler room with an eye-pleasing design. With the addition of a UPS Anti-freeze system and magnetic separator, our heat pump is properly protected. The compact form and thoughtful design makes the entire installation take up less space while providing easy access for maintenance.



5







Polish Brand Polish Guarantor

5-year guarantee

Antifreeze system


Magnetic filter

6/9 kW electric instantaneous water heater

🝸 kensol



ENERGY FOR THE FUTURE



| 1. Pressure | gauge |
|-------------|-------|
|-------------|-------|

- 2. Air Vent
- 3. Circulation pump
- 4. Anitfreezing system water pump
- 5.3 stage back up elec-
- tric heater
- 6.3-way valve
- 7. Flow from heat pump
- 8. Return to heat pump 9. Return from system
- 10. Central heating flow
- 11. DHW flow
- 12. Anti freezing System UPS
- 13. Fuse box
- 14. Power sockets

15. Heat pump controller

| Specifications | КТНВ17 |
|---|--|
| | |
| Diverter valve | DN25 |
| Electric heater | 3 x 3 kW (level adjustable) |
| Circulation pump | IBO MAGI-H 25-120 |
| Anti-freeze kit | SARG1 |
| Magnetic filter | magnet 1,26T, 800µm mesh, KVS=13,6m³/h |
| Safety valve | 3 bar |
| Size of hydraulic connections | GW 5/4" |
| Dimensions H x W x D | 530 mm x 650 mm x 295 mm |
| Weight | 35 kg |
| Noise | < 35 dB |
| Recommended electrical supply | min. 3 x 16A, 230V AC, 50Hz |
| Recommended power cable | 5 x 2,5 mm² |
| Recommended cable for sensor with SARG1 | 2 x 1 mm² |
| | |

Specifications

KTHB6-10, KTHB14

| Diverter valve | DN25 |
|---|--|
| Electric heater | 3 x 2 kW (level adjustable) |
| Circulation pump | IBO 80/100* |
| Anti-freeze kit | SARG1 |
| Magnetic filter | magnet 1,26T, 800µm mesh, KVS=13,6m³/h |
| Safety valve | 3 bar |
| Size of hydraulic connections | GW 1" |
| Dimensions H x W x D | 530 mm x 650 mm x 295 mm |
| Weight | 35 kg |
| Noise | < 35 dB |
| Recommended electrical supply | min. 3 x 10A, 230V AC, 50Hz |
| Recommended power cable | 5 x 2,5 mm² |
| Recommended cable for sensor with SARG1 | 2 x 1 mm² |

Due to the continuous technical innovation, technical data above might be of modification accordingly. KENSOL informs of its sole right to make modifications at anytime without further notice.

v1.05.2023